



FASSI GROUP



PIAF 10RE

Vertical Mast Boom Lift

Built to last

MAIN FEATURES

Working height 9,92 m / 32,54 ft

Horizontal outreach 3,51 m / 11,51 ft

Chassis width 1,00 m / 3,28 ft

0 Tail swing

Electric drive


▲ STANDARD EQUIPMENT

- Non-marking rubber wheels
- Platform with protection bar
- 200kg load capacity
- 24V 215 Ah Battery
- Centralized battery filling
- On-board H/F charger
- Non-continuous 356 ° turret rotation
- 25% gradeability
- Possible to work at maximum height
- On-board diagnostic colour LCD console
- Sling and tow rings
- Battery charge indicator
- Tilt indicator with alarm
- Overload sensor
- Flashing lights
- Hour meter

★ ACCESSORIES & OPTIONS

- Easy access to the platform by an entry gate
- Compressed air line
- Power supply in the platform
- Movement cut off when tilt > 2°
- Motion alarm
- Anti-crushing (ACS) system
- Customer colour(s) paint

PIAF 10RE



Working height	9,92 m / 32,54 ft
Floor height	7,92 m / 25,98 ft
Maximum horizontal outreach	3,51 m / 11,51 ft
Load capacity (Interior, 2 people, wind 0 km/h)	200 kg / 441 lbs
Load capacity ((Exterior, 1 people, wind < 45km/h)	200 kg / 441 lbs

A Length	2,78 m / 9,12 ft
B Chassis width	1,00 m / 3,28 ft
C Platform length	0,80 m / 2,62 ft
D Platform width	0,93 m / 3,05 ft
E Height	1,99 m / 6,52 ft
F Wheelbase	1,20 m / 3,93 ft
G Ground clearance	8,2 cm / 0,27 ft

Turret rotation	356° NC
Drive speed (stowed)	5,5 km/h / 3,41 mph
Drive speed (raised)	0,9 km/h / 0,56 mph
Gradeability (stowed)	25%
Maximum tilt	2°
Inside turning radius (Ri)	0,52 m / 1,70 ft
Outside turning radius (Re)	2 m / 6,56 ft
Total weight	2850 kg / 6283 lbs
Ground pressure	932 kN/m ²



This product complies with European regulations in force.
Due to our constant improvement policy, ATN reserves the right to many any modifications without any prior notice.

RT : Working circle
Ri : Inside turning radius
Re : Outside turning radius

